

PERFECT PRIMER CPF - 100

CHEMPROOF

콘크리트 바탕강화제

Waterproofing System

GROUND REINFORCING AGENT

● 특징

CPF - 100 바탕 강화제는 콘크리트 양생 후 시간경과에 따른 중성화로 열화 발생 및 강도저하, 조밀성이 현저히 떨어지는 부실면의 바탕강도를 높여주어 바탕면에 방수성능을 극대화하여 수분침투를 방지합니다.

● 용도

- 옥상, 창고바닥, 주차장 내부 등
- 시공 전 바닥면 강화용
- 수용성 방수 시 프라이머 용

● 특성

- 내열성, 내후성, 내동결, 융해성 우수 / 염분, 알칼리 등에 대한 저항성이 우수합니다.
- 미장, 콘크리트 상재, 구체면과 부착력이 우수 / 콘크리트에 무해하며 무기질 무독성입니다.

● 주의사항

1. 시공부위를 최대한 건조시키고 시공 후 12시간 이내에는 물 접촉을 금하십시오.
2. 5°C 이상 35°C 이하에서 시공하도록 하십시오.
3. 보관 시 동결에 주의하십시오.
4. 실내에 보관하십시오.

● 사용방법

1. 시공부위의 기름, 이끼, 유분은 깨끗이 청소합니다.
2. 사용 시 반드시 원액을 사용하여 에어리스, 롤러, 붓 등으로 도포합니다.

● 포장단위 / 색상

- 4Liter, 18Liter Pail / 색상 : 유백색



● Feature

CPF - 100 is a After curing concrete, it neutralizes with time, prevents deterioration of strength, deteriorates strength, and improves the strength of poorly densely packed surface to prevent moisture penetration.

● Uses

- Roof, warehouse floor, interior
- For strengthening the floor before construction
- For water-soluble primers

● Characteristic

- Excellent in heat resistance, weatherability, freezing and solubility.
- Excellent resistance to salt and alkali.
- Plastering, concrete, excellent concrete and adhesion / harmless to concrete, inorganic and non-toxic.

● Precautions

1. Dry the construction site as much as possible and avoid contact with water within 12 hours after installation.
2. Please do not apply more than 5°C to 30°C.
3. Please be careful about freezing when storing.
4. Please keep it inside.

● How to use

1. Clean the oil, moss and dirt on the construction site thoroughly.
2. Always use the original solution with a brush, roller or airless.

● Packing Unit & Color

- 4Liter, 18Liter Pail / Color : White



* For further information, please refer to Material Safety Data Sheet (MSDS).
* 기타 상세한 자료는 물질안전보건자료 (MSDS)를 참조하십시오.

Supplier in Myanmar



Yangon Branch : Room No. 6C, Aye Yeik Thar Condominum, No. (483) ,
Aye Yeik Thar (2) Street, Bahan Tsp. Yangon, Myanmar

MP : 09-44476-7044 (Myanmar & English)
MP : 09-44476-7045 (Korean & English)

Sole Distributor by
GHI
GLOBAL HIGHTECH INDUSTRY

16gil - 6 Jinjang Bukgu, Ulsan, Korea
Tel : 82-52-298-2259 , Direct MP : 82-10-9300-2259
E-mail : steve@ghi.cc Myanmar MP : 09-42173-9844 (Korean)



PERFECT PRIMER CPF - 100

CHEMPROOF

콘크리트 바탕강화제

Waterproofing System

GROUND REINFORCING AGENT

● Feature

CPF-100 ကို ကွန်ကရစ်သွန်းလောင်းပြီးချိန်တွင် အသုံးပြုနိုင်ပါသည်။ အချိန်ကာလကြာမြင့်ခြင်းကြောင့် ဖြစ်ပေါ်လာသော ဟောင်းနွမ်းမှုကုန်ရာပြင်တွင်လည်း အသုံးပြုနိုင်ပါသည်။ CPF-100 ကိုအသုံးပြုပါက အစိစာထိုးဖောက်မှုကို ကာကွယ်ပေးပြီး ရေစိုခံစွမ်းရည်ကို မြင့်တက်စေပါသည်။

● Uses

- ကြမ်းခင်း၊ ကုန်သိုလှောင်ရုံကြမ်းခင်း၊ interior များတွင်အသုံးပြုနိုင်ပါသည်။

● Characteristic

- အပူဒဏ်ခံနိုင်ခြင်း၊ ရာသီဥတုဒဏ်ခံနိုင်ခြင်း၊ သိမ်းဆည်းနိုင်ခြင်း၊ အအေးဒဏ်ခံနိုင်ခြင်း။
- Salt and Alkaline ဒဏ်ခံနိုင်ခြင်း။
- ကပ်အားကောင်းခြင်း၊ ကွန်ကရစ်တွင်စွဲခြင်း၊ အသုံးပြုသူများအတွက် အဆိပ်အတောက်မရှိခြင်း။

● Precautions

1. Primer သုံးပြီး ၁၂ နာရီအတွင်း ရေနှင့်ထိတွေ့ခြင်း မပြုလုပ်ရ၊ အလျင်အမြန် ခြောက်သွေ့စေရမည်။
2. 30°C ထက် ပိုသောအပူချိန်တွင် အသုံးမပြုပါနှင့်။
3. သိမ်းဆည်းရာတွင် မအေးခဲစေရန်သတိပြုပါ။
4. အဆောက်အဦးအတွင်း၌သာ သိမ်းဆည်းပါ။

● How to use

1. မျက်နှာပြင်ရိတ်များ၊ မြက်ပင်များ၊ ဖုန်မှုန့် များအား သေချာစွာရှင်းလင်းပါ။
2. Brush (သို့) Roller (သို့) airless spray တို့ဖြင့် သုံးနိုင်ပါသည်။

● Packing Unit & Color

- 4Liter, 18Liter Pail / Color : White



● Feature

CPF - 100 is a After curing concrete, it neutralizes with time, prevents deterioration of strength, deteriorates strength, and improves the strength of poorly densely packed surface to prevent moisture penetration.

● Uses

- Roof, warehouse floor, interior
- For strengthening the floor before construction
- For water-soluble primers

● Characteristic

- Excellent in heat resistance, weatherability, freezing and solubility.
- Excellent resistance to salt and alkali.
- Plastering, concrete, excellent concrete and adhesion / harmless to concrete, inorganic and non-toxic.

● Precautions

1. Dry the construction site as much as possible and avoid contact with water within 12 hours after installation.
2. Please do not apply more than 5°C to 30°C.
3. Please be careful about freezing when storing.
4. Please keep it inside.

● How to use

1. Clean the oil, moss and dirt on the construction site thoroughly.
2. Always use the original solution with a brush, roller or airless.

● Packing Unit & Color

- 4Liter, 18Liter Pail / Color : White



* For further information, please refer to Material Safety Data Sheet (MSDS).
* 기타 상세한 자료는 물질안전보건자료 (MSDS)를 참조하십시오.

Supplier in Myanmar



Yangon Branch : Room No. 6C, Aye Yeik Thar Condominium, No. (483) ,
Aye Yeik Thar (2) Street, Bahan Tsp. Yangon, Myanmar

MP : 09-44476-7044 (Myanmar & English)
MP : 09-44476-7045 (Korean & English)



16gil - 6 Jinjang Bukgu, Ulsan, Korea
Tel : 82-52-298-2259 , Direct MP : 82-10-9300-2259
E-mail : steve@ghi.cc Myanmar MP : 09-42173-9844 (Korean)



Registered ISO 9001 , 14001