

Summary

Perfect Seal CS-222 is a one component product of neutral curing type. It is a modulus sealant that combines both workability and economy. It is a versatile sealant that exhibits excellent adhesion without primer treatment to most building materials.

Feature

- ☒ It is a non-acetic acid type silicone sealant which is neutral curing type and has no irritating odor.
- ☒ It is easy to use as one-component type and has excellent workability.
- ☒ Excellent adhesion to various materials (concrete, glass metal, plastic, aluminum, etc.) without primer.
- ☒ Sealing is possible for various applications. (Various doors, glass window frames, glazing, etc.)
- ☒ It is excellent in resilience, motion resistance, weather resistance and low temperature workability.

Product property [KSF-4910 (F20HM)]

Contents	Result	Contents	Result
Hardening type	Neutral hardening type	Elongation	300~400% (ASTM D 412)
Shape	Paste	Motion availability	±20% (ASTM C 419)
Surface hardening	Within 30minutes (25°C/50°C RH)	Elastic restoring force	60% or more
Time	7~14 day	Elongation rate of jointed butterfly	160%
Specific gravity	0.98±0.02(Clear) 1.45±0.02 (Filler)	Tensile stress	23°C/-20°C : 0.4Nmm ² or more/ 0.6Nmm ² or more
Hardness	Shore: 25~30 (ASTM D 2240)	Adhesive	Clear at 23°C
Tensile strength	10~15kg/cm ² (ASTM D 412)	Adhesion after exposure to artificial light	Clear

Uses

- ☒ General sash and window frame glazing of aluminum and wood.
- ☒ Glazing and sealing of glass, metal, tile, celamic, PVC, aluminum etc.

Color

- ☒ White, gray, clear, brown, black / green, ivory, cherry, light gray, blue, gold, red and so on.
- ☒ The basic colors are underlined five colors. please check other colors before ordering.

Storage and Handling Precautions

- ☒ Before using the product, please cut off the nozzle properly.
- ☒ Please clean the area to be used. (Such as oil, moss, oil, debris, etc.)
- ☒ After use, use a putty knife(rubber, silicone) or other apparatus to smooth the surface.
- ☒ Store at temperatures below 5°C~35°C.
- ☒ Please keep out of reach of children.
- ☒ Please refer to Material Safety Data Sheet (MSDS) before use.

Hazard Pictogram



warning

Packing unit

- 270ml Cartridge 25EA/Box


Manufacturer Information

- GHI CO.,LTD.**
A/S Phone: 080-295-8259 Tel:+82-298-2259
E-mail: hq@eghi.biz , ghi2259@naver.com
www.ghi.cc www.indmall.co.kr www.dreammall.shop



CHEMGUARD

Subsidiary materials



Silicone Gun



Finishing Pads (silicone)



Silicone Nozzle

This Product Data Sheet provides information about our products based on our own test results and related materials. This data does not guarantee the accuracy and results of the products. In addition, this information may be changed by new knowledge, testing, etc. and limits its use for any purpose other than providing information