

Summary

CS-290NF is mainly used for filling, adhesive, soundproofing, dustproof, etc. It has no shrinking and metal corrosiveness. It is an elastic material that maintains elasticity and adhesion, and is excellent in water resistance, heat resistance and cold resistance.

Feature

- It is easy to work and has no odor.
- It is not attached to the hand and can be easily used by anyone.
- It is flame retardant and the risk of fire is low.

General Properties

- Appearance : Gray putty
- Solid content : 95% or more (KSM 2095-6)
- Specific gravity : 1.865 (KSM 2095-5)
- Odor : A little rubber smell
- cold resistance : No cracks at -25°C for 24 hours.
- Adhesiveness : 0.5kg/cm²
- Storage duration : 18 months at room temperature (daylight and humidity free)

Uses

- Sealing and filling of ships, automobiles, and construction.
- Sealing of piping line, sealing part of outer cover of PE Cable.
- Temporary fixing of window frames and glass.

How to use

- Remove moisture, dirt, oil and dirt from the surface. Peel off the vinyl before use.
- When using the product, apply some pressure to the surface to be used and fill and seal it.

Storage & Handling Precautions

- Do not smell deliberately. Keep the remaining product in a cool, sealed place after use.
- Use of any other purpose is prohibited. - Please keep out of reach of children.
- For further safety information, please refer to the Material Safety Data Sheet (MSDS).

Packing unit

- (500g*2ea)* 10EA/Box

Manufacturer Information

- GHI CO.,LTD.
- E-mail: hq@eghi.biz, ghi2259@naver.com
- Website: www.eghi.biz www.dreammall.shop



This Product Data Sheet provides information about our products as a result of our own tests and the results of external testing, and DATA does not guarantee the accuracy and results of our products. In addition, this information may be changed by new knowledge and testing without prior notice, and is prohibited from use for any purpose other than providing information.



Net:10kg